

FIG. 1A
(PRIOR ART)




FIG. 1B
(PRIOR ART)




FIG. 1C
(PRIOR ART)





FIG. 1D
(PRIOR ART)



457240-6686580

APPROVED	C. G. FIG.	
By	CLASS	SUBCLASS
DRAFTSMAN		

FIG. 2A(PRIOR ART)





FIG. 2B (PRIOR ART)



467220-6E8/6E8D

FIG. 3C

S4




FIG. 3D

S5




FIG. 3E

S6





FIG. 3F

S7



08897839.019
267220-68826880

FIG. 4A





FIG. 4B



08897839-073197

APPROVED	O. G. FIG.	
BY	CLASS	SUBCLASS
DRAFTSMAN		

Stress change in
multiple laminated layers
and crack generation

FIG. 5A (μm)





FIG. 5B




672/0-EE2/6880

APPROVED	O. G. FIG.	
BY	CLASS	SUBCLASS
DRAFTSMAN		

FIG. 6


Stress change per unit thickness
due to humidity absorption



00897839-072197



26T220" 6E826880

APPROVED	O. G. FIG.	
BY	CLASS/SUBCLASS	
DRAFTSMAN		



APPROVED	O. G. FIG.	
BY	CLASS	SUBCLASS
DRAFTSMAN		

26T220-6E846880



No bias is applied in all events

667240 68826880

FIG. 8A




FIG. 8B

Film forming temperature 400°C
 Film forming rate 100nm/分




FIG. 8C




FIG. 9A




FIG. 9B





FIG. 9C



08997029-0219
2012-06-06

FIG. 10A




FIG. 10B

